

Sans commentaire

Juste 2 astuces pour ne pas afficher les commentaires (par exemple, utile lors de la lecture de fichiers de configuration)

Base egrep

```
egrep -v "#|$^" MonFichierDeConf
```

Base sed

```
alias nocomments='sed '\''/^[[[:blank:]]*#/d;s/#.*//;/^$/d'\''
```

Puis

```
cat MonFichierDeConf | nocomments
```

Exemples

```
ragnarok@fenrir:~$ cat /etc/nginx/sites-available/default
##
# You should look at the following URL's in order to grasp a solid
understanding
# of Nginx configuration files in order to fully unleash the power of Nginx.
# https://www.nginx.com/resources/wiki/start/
#
https://www.nginx.com/resources/wiki/start/topics/tutorials/config_pitfalls/
# https://wiki.debian.org/Nginx/DirectoryStructure
#
# In most cases, administrators will remove this file from sites-enabled/
and
# leave it as reference inside of sites-available where it will continue to
be
# updated by the nginx packaging team.
#
# This file will automatically load configuration files provided by other
# applications, such as Drupal or Wordpress. These applications will be made
# available underneath a path with that package name, such as /drupal8.
#
# Please see /usr/share/doc/nginx-doc/examples/ for more detailed examples.
##

# Default server configuration
#
```

```
server {  
    listen 80 default_server;  
    listen [::]:80 default_server;  
  
    # SSL configuration  
    #  
    # listen 443 ssl default_server;  
    # listen [::]:443 ssl default_server;  
    #  
    # Note: You should disable gzip for SSL traffic.  
    # See: https://bugs.debian.org/773332  
    #  
    # Read up on ssl_ciphers to ensure a secure configuration.  
    # See: https://bugs.debian.org/765782  
    #  
    # Self signed certs generated by the ssl-cert package  
    # Don't use them in a production server!  
    #  
    # include snippets/snakeoil.conf;  
  
    root /var/www/html;  
  
    # Add index.php to the list if you are using PHP  
    index index.html index.htm index.nginx-debian.html;  
  
    server_name _;  
  
    location / {  
        # First attempt to serve request as file, then  
        # as directory, then fall back to displaying a 404.  
        try_files $uri $uri/ =404;  
    }  
  
    # pass PHP scripts to FastCGI server  
    #  
    #location ~ \.php$ {  
    #    include snippets/fastcgi-php.conf;  
    #  
    #    # With php-fpm (or other unix sockets):  
    #    fastcgi_pass unix:/run/php/php7.4-fpm.sock;  
    #    # With php-cgi (or other tcp sockets):  
    #    fastcgi_pass 127.0.0.1:9000;  
    #}  
  
    # deny access to .htaccess files, if Apache's document root  
    # concurs with nginx's one  
    #  
    #location ~ /\.ht {  
    #    deny all;  
    #}  
}
```

```
# Virtual Host configuration for example.com
#
# You can move that to a different file under sites-available/ and symlink
# that
# to sites-enabled/ to enable it.
#
#server {
# listen 80;
# listen [::]:80;
#
# server_name example.com;
#
# root /var/www/example.com;
# index index.html;
#
# location / {
#     try_files $uri $uri/ =404;
# }
#}
```

```
ragnarok@fenrir:~$ cat /etc/nginx/sites-available/default | nocomments
server {
    listen 80 default_server;
    listen [::]:80 default_server;
    root /var/www/html;
    index index.html index.htm index.nginx-debian.html;
    server_name _;
    location / {
        try_files $uri $uri/ =404;
    }
}
```

```
ragnarok@fenrir:~$ egrep -v "#|^$" /etc/nginx/sites-available/default
server {
    listen 80 default_server;
    listen [::]:80 default_server;
    root /var/www/html;
    index index.html index.htm index.nginx-debian.html;
    server_name _;
    location / {
        try_files $uri $uri/ =404;
    }
}
```

From:
<https://cbiot.fr/dokuwiki/> - Cyrille BIOT



Permanent link:
<https://cbiot.fr/dokuwiki/nocomments?rev=1594228838>

Last update: **2020/07/08 19:20**